

**YDEEVNEDEKLARATION (DK)
DECLARATION OF PERFORMANCE (UK)
LEISTUNGSERKLÄRUNG (DE)**

No. 457501-1

Kongerslev d. 1. Juni 2019

Producenten:
The manufacturer:
Der Hersteller:

JET Domex A/S, Neptunvej 6, 9293 Kongerslev Danmark

erklærer under eget ansvar, at produktet:
declare under our sole responsibility, that the product:
erklært hiermit eigenverantwortlich, dass das Product:

**Polycarbonate Roof Light, Type HV10, HV20, HV30,
HV30+/RY10, RY20, RY30/PL10, PL20, PL30
with or without upstand**

for den tilsigtede anvendelse:
for the intended use:
für der bezwecken verwendung:

**lighting by means of daylight and of ventilating interior
spaces by means of opening devices**

med kontrolsystem (AVCP):
with the control procedure (AVCP):
mit der Steuerung (AVCP):

System 3

til hvilket denne erklæring henfører, er i overensstemmelse med den
følgende standard(er) eller andre normgivende dokument(er):
to which this declaration relates is in conformity with the following
standard(s) or other normative document(s):
auf das sich diese Erklärung bezieht, mit der/den folgenden Norm(en)
oder normativen Dokument(en) überinstimmt:

DS/EN1873:2006

i henhold til direktivets bestemmelser:
following the provisions of directive:
gemäss den Bestimmungen der Rechtslinie:

Regulation (EU) No 305/2011

Specifications	HV10	HV20	HV30	HV30+	RY20	RY30	PL10	PL20	PL30
Resistance to upward load	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Resistance to downward load	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Durability	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Air permeability	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Direct airborne sound insulation	20dB	22dB	23dB	NPD	22dB	23dB	20dB	22dB	23dB
Luminous transmittance (Clear)	65%	46%	35%	NPD	46%	35%	65%	46%	35%
Luminous transmittance (Opal)	60%	42%	29%	NPD	42%	29%	60%	42%	29%
Reaction to fire, wooden frame	D-s2, d0	D-s2, d0	D-s2, d0	D-s2, d0	D-s2, d0	D-s2, d0	D-s2, d0	D-s2, d0	D-s2, d0
Reaction to fire, Top plate	B-s1, d0	B-s1, d0	B-s1, d0	B-s1, d0	B-s1, d0	B-s1, d0	B-s1, d0	B-s1, d0	B-s1, d0
Resistance to fire	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD
External fire performance	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Water tightness	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Small, hard body	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD
Large, soft body	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD

Thermal transmittance	HV10	HV20	HV30	HV30+	RY20	RY30	PL10	PL20	PL30
88 x 193 cm (Fixed/Ventilated)	1,9/1,9	1,4/1,5	1,2/1,2	1,0/1,1	1,6/1,6	1,2/1,3	1,8/1,9	1,3/1,4	1,1/1,2
100 x 100 cm (Fixed/Ventilated)	1,9/1,9	1,4/1,5	1,2/1,3	1,0/1,1	1,5/1,6	1,2/1,3	1,7/1,8	1,3/1,3	1,1/1,2
100 x 200 cm (Fixed/Ventilated)	1,9/2,0	1,4/1,5	1,2/1,3	1,0/1,1	1,6/1,6	1,2/1,3	1,8/1,9	1,3/1,4	1,1/1,2
100 x 240 cm (Fixed/Ventilated)	1,9/2,0	1,4/1,5	1,2/1,2	1,0/1,0	1,6/1,6	1,2/1,3	1,8/1,9	1,3/1,4	1,1/1,2
120 x 120 cm (Fixed/Ventilated)	1,9/2,0	1,5/1,5	1,2/1,3	1,0/1,1	1,5/1,6	1,2/1,3	1,8/1,8	1,3/1,4	1,1/1,2
120 x 240 cm (Fixed/Ventilated)	2,0/2,0	1,4/1,5	1,2/1,2	1,0/1,1	1,6/1,6	1,2/1,3	1,9/1,9	1,3/1,4	1,1/1,2

Calculated on insulated upstand 30cm above roof construction
Values in W/m²K



Henrik Dall Lauridsen, CEO